

ALCOR – II C

CNC Profile Machining and Cutting Center (8 Servo Axis – 7 Machining Axis for Alu)


Automation by
FANUC




The servo 8-axis CNC profile profile machining and cutting center **ALCOR - II C** has been developed to carry out all-in-one cutting, milling, drain channel opening, punching and marking operations on profiles, and to perform special non-standard operations (punching, channel opening etc.) on different profiles. Thanks to its individually operating units, **ALCOR - II C** has been designed to offer maximum efficiency in less time.





7 units of fan cooled spindle motors that can function and be positioned as different angles enables an unlimited operational capability on 4 surfaces of the profile.



Thanks to the feeding capacity of 10 profiles, the conveyor structure enables batch processing, letting the machine to be used in the most efficient manner.



The cutting unit with a 550 mm diameter saw blade for cutting at every angle between 30° and 150° offers a wide cutting range to users.







ALCOR – II C

CNC Profile Machining and Cutting Center (8 Servo Axis – 7 Machining Axis for Alu)

CONFIGURABLE SPINDLES

ALCOR - II C has 7 spindle motors and can be configured within the 14 slots on the machine before leaving the factory.



ALCOR – II C

CNC Profile Machining and Cutting Center (8 Servo Axis – 7 Machining Axis for Alu)

POSITIONING SPEED

X1 Axis (Longitudinal)	40 m/min
Y1 Axis (Lateral)	60 m/min
Z1 Axis (Vertical)	60 m/min
Z2 Axis (Cutting unit vertical movement)	42 m/min
C2 Axis (Cutting unit rotation)	166°/sec
XL Axis (Drive robot)	90 m/min

AIR

Pressure	6-8 Bar
----------	---------

ELECTRICAL

Max. Power	31.35 kW
Voltage	400V 3N PE AC
Frequency	50-60 Hz

CUTTING UNIT

Cutting angles span	30° / 150°
Saw blade diameter	550 mm
Saw blade motor power	3kW - 4HP

MILLING UNIT

Fan cooling spindles	7
Spindle power	3 kW
Maximum speed	18.000 rpm
Tool holder	ER 20

LOADING AND UNLOADING UNIT

Minimum profile loading length	1200 mm
Maximum profile loading length	7500 mm
Minimum profile unloading length (90° - 90°)	270 mm
Profile loading capacity	10
Automatic chip discharge conveyor unit	●
Belt-driven profile discharge unit	○

GRIPPER AXIS TRAVEL

YL Axis (Lateral) min. / max.	20 mm / 117 mm
ZL Axis (Vertical) min. / max.	20 mm / 115 mm

CONTROL UNIT

Industrial PC - Touch Screen	15"
Data transfer over remote network connection, Ethernet and USB	●
Barcode writer	●
Compatibility with optimization programs	●
Compatibility with CAM programs	○
Camquix CAM software	●

OPERATIONAL AREA

Automatic lubrication in processing area	●
Cabinet providing protection in processing zone	●
FESTO pneumatic system	○

● Standard ○ Optional