



## Features

Used for lock, handle, hinge and latch slot and channel opening processes with rotating the profile on 3 surfaces of aluminum and plastic profiles.

- Copy assembly matching the process
- · Ability to open various channels independently of the copy assembly with profile gauges
- Pneumatic clamps
- Independently operating motors
- Independent milling process on 3 different surfaces

## Standard Equipments

- Cooling system
- 8 mm milling cutter
- Profile gauge
- **Optional Equipments**
- Special copy assembly5 -10 mm milling cutter



			(×3)		dø V		đ Z2 0		Z1 1 1 1 1 1 1 1 1 1 1 1 1 1	Z2			- <u></u>	La Sta
HP kW		Hz	ا (230 V)	ø D	ø d	X1	Y1	Z1	X2	Y2	Z2	Air Pressure	Air Consumption	l x w x h (mm)
1,5 1,1	12000 r.p.m	200	7A	8 mm	8 mm	460 mm	210 mm	210 mm	430 mm	240 mm	145 mm	6 - 8 bar	9 L / min.	2815 x 1430 x 1835 293 kg

Özçelik Makina continuously improves its products and offers new and modern solutions for PVC and Aluminum Profile Processing. Accordingly, Özçelik reserves the right to change the information in this document without notice. All dimensions and weights are reference values. Valid from January 2023