



FEATURES

Used for cutting window strips of plastic profiles at an angle of 45°

- Pneumatic cutting
- Automatic returning to process starting point
- Conveyor system with measuring equipmentCutting and conveying speed adjustment


STANDARD EQUIPMENTS

- Ø100 mm saw blade (2 pcs)
- Ø200 mm saw blade (2 pcs)
- · Strip mold
- Conveyor

OPTIONAL EQUIPMENTS

- Special mold
- Single-phase system
- Bluetooth Caliper
- Bluetooth Caliper





			(x2)	n	ØD1	Ød		<u>S2</u> (x2)	2)	CA		Jy 2		← I Ŏ <u></u> , IIII ←	A Reg
HP kW		3∼ Hz	l (400 V)	ø D1	ø D2	ød	S1	S2		CA	x max.	y max.	Air Pressure	Air Consumption	l x w x h (mm)
1,5 1,1	3000 r.p.m	50 60	4,6 A	200 mm	100 mm	32-22 mm	2 mm	4 mm	3000 r.p.m	45°	50 mm	30 mm	6 - 8 bar	20 L / min	1020 x 5985 x 1375 235 kg

Özçelik Makina continuously improves its products and offers new and modern solutions for PVCand Aluminum Profile Processing. Accordingly, Özçelik reserves the right to change the information in this document without notice. All dimensions and weights are reference values. Valid from January 2025